



Beautiful Made Easy

TIMELESS CLASSIC

8 MM HDF LAMINATE FLOORING AC4



*Actual color of the product may vary due to batch difference

WALNUT HERITAGE
TC-8001
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)



*Actual color of the product may vary due to batch difference

ROYAL TEAK
TC-8002
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)



*Actual color of the product may vary due to batch difference

HONEY OAK
TC-8003
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)



*Actual color of the product may vary due to batch difference

NATURAL OAK
TC-8004
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)



*Actual color of the product may vary due to batch difference

GOLDEN OAK
TC-8005
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)



*Actual color of the product may vary due to batch difference

RUSTIC WALNUT
TC-8006
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)



*Actual color of the product may vary due to batch difference

CLASSIC OAK
TC-8007
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)



*Actual color of the product may vary due to batch difference

SCANDINAVIAN OAK
TC-8008
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)



*Actual color of the product may vary due to batch difference

SILVER GREIGE OAK
TC-8009
Size : 47.95" x 7.79" x 8.0 mm

8 pcs / Carton
(20.76 Sqft)


TECHNICAL SPECIFICATIONS

Symbol	Item	Standard	Requirement (Specimen:8mm)	Result
	Abrasion Resistance	EN 13329	Type of wheel: CS-0 Load: (5.4±0.2) N/wheel Abrasive paper: S-42(P180) ≥2000 rev. AC4	Abrasion cycles: 2100 cycles, Abrasion clas: AC4
	Dynamic coefficient of friction	EN 14041:2004	≥ 0.30	Class DS
	Thickness Swelling	EN 13329	≤18 %	Pass
	Locking strength	EN 13329	Condition: 23±2C, 50±5%RH, 24h. Loading rate: 5mm/min	Long side(X): fmax=2.8kN/m; f0.2mm=1.9kN/m Short side(Y): fmax=3.0kN/m; f0.2mm=2.5kN/m
	Squareness	EN 13329	≤0.20mm	Pass
	Straightness	EN 13329	≤0.30mm	Pass
	Openings and Height difference	EN 13329	Openings between elements: Oaver - age≤0.15mm Omax.≤0.20mm Height difference between elements: Haverage≤0.10mm Hmax.≤0.15mm	Pass
	Flatness	EN 13329	concave: ≤ 0,15% convex:≤ 0,20% concave:≤ 0,50% convex:≤ 1,00%	Pass
	Residual indentation	EN 13329	Applied load: 500N Load time: 150min Recovery time: 150min Residual indentation ≤ 0.05 mm	Excellent Residual indentation: 0.01mm
	Castor chair test	EN 13329	Cycles: 25000 Load: 90kg Type of castors: Type W	No visible damage
	Effect of a furniture leg	EN 13329	Foot type and applied mass: Type 0 (32kg) Testing speed: 0.20m/s	X direction: No visible damage Y direction: No visible damage
	Stain resistance	EN 13329	Group 1~3	Rating 5: No change
	Impact Resistance Large ball	EN 13329	Mass of steel ball: (324±5)g Diameter of steel ball: (42.8±0.2)mm ≥1600mm	Impact Height:1600mm, no visible damage.
	Impact Resistance Small ball	EN 13329	≥90mm	Impact Height:90 mm, no visible damage.
	Formaldehyde Release	EN 717-1	Class E1 ...≤0.124 mg/m³ E2 ...>0.124 mg/m³	Class E1
	Reaction to fire	EN 14041:2004/ AC:2006	Class Cfl≥ 4.5KW.m-2	Class Cfl-s1
	Pentachloro - phenol (PCP)	EN 14041:2004/ AC:2006	0.1 mg/kg	ND

UNIQUE FEATURES



* Moisture Resistance



* Stain Resistant



Click & Lock



Eco Friendly

* Under standard condition only. It does not cover chemical stains

STANDARD INSTALLATION GUIDELINE

1. **Measurement:** Check the room dimension by getting it measured by a professional installer.
2. **Prepare Subfloor:** Ensure the subfloor is clean, dry, and level. Repair any imperfections and remove debris.
3. **Acclimate Planks:** Let the HDF Laminate planks acclimate to the room for at least 48 hours before installation.
4. **Cutting Planks:** Use proper cutting tools to cut the planks. Measure and mark accurately.
5. **Layout Planning:** Plan the layout, ensuring the first row is straight. Avoid narrow plank widths at walls.
6. **Cleaning:** Mop the floor with clean water. Avoid using any harsh chemical as they can damage the surface.



Beautiful [♦]Made Easy

TIMELESS CLASSIC

8 MM HDF LAMINATE FLOORING AC4



www.excelwallpapers.com